

EDAN



iM60 Patient Monitor



iM60
Patient Monitor



EDAN Edan Instruments, Inc.

- 3/F – B, Nanshan Medical Equipments Park, Nanhai Rd 1019#, Shekou, Nanshan Shenzhen, 518067 P.R. China
- Tel: +86-755-26898326 • Fax: +86-755-26898330 • www.edan.com.cn • Email: info@edan.com.cn
- All rights reserved. Features and specifications are subject to change without notice



ENG-PM-iM60-V1.3-20140115



Care for Health

EDAN

iM60 Patient Monitor

10.4"

Maximum 11 Waveforms



> Configurations

- **Basic Measurements for Sub-acute Cares**
A full set of basic parameters including 3/5 lead ECG, HR, RESP, EDAN SpO₂ (NELLCOR optional), NIBP, PR, and 2-channel temperature is employed
- **Critical Measurements for Acute Cares**
The introduction of 2-channel invasive BP, cardiac output, and end tidal carbon dioxide may suit the requirements of most acute cares

> Reliable Algorithms

- iSEAP™ ECG algorithm optimized for arrhythmia detection, pacemaker detection, and HR measurement
- iMAT™ SpO₂ algorithm with outstanding motion resistance and low perfusion resistance performance
- iCUFFS™ NIBP algorithm optimized for cardiac patients, hypertensive patients, and neonatal patients

> Multiple Display Modes



Standard Display

Large Font

Trend View

OxyCRG

Bed to Bed

> End tidal Carbon Dioxide for Intubated/Non-Intubated Patients



EDAN G2 CO₂ (Sidestream)

- Superior water trap design for accurate monitoring
- iCARB™ algorithm with intelligent CO₂ pseudo wave identification technology
- Multiple sampling accessories as options for adult, child and neonate patients

Respironics CO₂ (Mainstream/Sidestream)

- Plug & play module design
- Dehumidification tube instead of water trap
- Low sampling rate of 50ml/min suitable for all types of patients



No-fan Design Night Mode Pitch Tone Thermal Recorder



Internal Temp Storage:

1200 NIBP Measurement Review	120 h Trend Review	60 Alarm Review	120 s Frozen Waveform
--	------------------------------	---------------------------	---------------------------------